



Up-to-date Practice Test with Latest Questions and Answers covering latest syllabus and topics of the exam. Makes you ready to face actual exam.



NCEES-PE-Civil-WRE Practice Questions
NCEES-PE-Civil-WRE Practice Test
NCEES-PE-Civil-WRE Practice Exam
NCEES-PE-Civil-WRE Exam Questions
NCEES-PE-Civil-WRE Study Guide



killexams.com

NCEES

NCEES-PE-Civil-WRE

NCEES PE Civil Engineering: Water Resources and Environmental

ORDER FULL VERSION

<https://killexams.com/pass4sure/exam-detail/NCEES-PE-Civil-WRE>



Question 386:

An environmental engineer is assessing the impact of a sewage treatment plant on a nearby stream. If the plant discharges effluent with a biochemical oxygen demand (BOD) of 200 mg/L and the stream's flow is 3 m³/s, what is the total BOD load entering the stream from the plant in kilograms per day?

- A. 51,840 kg/day
- B. 21,880 kg/day
- C. 45,320 kg/day
- D. 65,000 kg/day

Answer: A

Explanation: The BOD load can be calculated as:

$$\text{BOD Load} = \text{Concentration} \times \text{Flow Rate} \times \text{Time}$$

Convert mg/L to kg/m³:

$$\text{Concentration} = 200 \text{ mg/L} = 0.2 \text{ kg/m}^3$$

Thus,

$$\text{BOD Load} = 0.2 \text{ kg/m}^3 \times 3 \text{ m}^3/\text{s} \times 86,400 \text{ s} = 51,840 \text{ kg/day}$$

Question 387:

A groundwater engineer is evaluating the effects of a contaminant plume in a confined aquifer. If the hydraulic conductivity is 20 m/day and the contaminant concentration decreases from 1,000 µg/L to 100 µg/L over a distance of 50 m, what is the attenuation factor?

- A. 0.1

- B. 0.5
- C. 0.7
- D. 10.0

Answer: D

Explanation: The attenuation factor is calculated as:

$$\text{Attenuation Factor} = \frac{C_1}{C_2} = \frac{1000 \mu\text{g}/L}{100 \mu\text{g}/L} = 10$$

Question 388:

A civil engineer is assessing the effect of urban runoff on a stream's DO levels. If the stream's DO was 8 mg/L before the runoff event and dropped to 5 mg/L after, what is the percentage change in DO?

- A. 20%
- B. 25%
- C. 37%
- D. 35%

Answer: C

Explanation: The percentage change in DO is calculated as:

$$\text{Percentage Change} = \frac{\text{Initial DO} - \text{Final DO}}{\text{Initial DO}} \times 100$$

Thus,

$$\text{Percentage Change} = \frac{8 - 5}{8} \times 100 = 37.5\%$$

Question 389:

An environmental scientist is evaluating the impact of nutrients on a lake's water quality. If the lake has a volume of $1,000,000 \text{ m}^3$ and the total phosphorus concentration is 0.2 mg/L , what is the total phosphorus load in kilograms?

- A. 0.2 kg
- B. 2 kg
- C. 20 kg
- D. 200 kg

Answer: D

Explanation: The total phosphorus load can be calculated as:

$$\text{Load} = \text{Concentration} \times \text{Volume}$$

Convert concentration to kg/m^3 :

$$\text{Concentration} = 0.2 \text{ mg/L} = 0.0002 \text{ kg/m}^3$$

Thus,

$$\text{Load} = 0.0002 \text{ kg/m}^3 \times 1,000,000 \text{ m}^3 = 200 \text{ kg}$$

Question 390:

A groundwater model indicates that a well is experiencing a drawdown of 5 m after 12 hours of continuous pumping. If the well has a radius of 0.1 m and the aquifer has a hydraulic conductivity of 10 m/day, what is the estimated specific yield of the aquifer?

- A. 0.01
- B. 0.05
- C. 0.1
- D. 0.15

Answer: B

Explanation: The specific yield can be calculated using the relationship:

$$\text{Specific Yield} = \frac{\text{Drawdown}}{\text{Time}} \times \frac{1}{\text{Hydraulic Conductivity}}$$

Thus,

$$\text{Specific Yield} = \frac{5 \text{ m}}{12 \times 3600 \text{ s}} \times \frac{1}{10 \text{ m/day}} = 0.05$$

Question 391:

A hydrogeologist is evaluating a confined aquifer that has a hydraulic conductivity of 25 m/day and a thickness of 30 m. If the aquifer is being recharged at a rate of 0.1 m/year, what is the estimated sustainable yield of the aquifer over an area of 2 hectares?

- A. 2000 m³/yr
- B. 1500 m³/yr
- C. 1600 m³/yr
- D. 1700 m³/yr

Answer: A

Explanation: The sustainable yield can be estimated using:

$$\text{Sustainable Yield} = \text{Recharge Rate} \times \text{Area}$$

Convert the recharge rate to meters:

$$\text{Recharge Rate} = 0.1 \text{ m/yr}$$

Convert area to square meters:

$$\text{Area} = 2 \text{ hectares} = 20,000 \text{ m}^2$$

Thus,

$$\text{Sustainable Yield} = 0.1 \text{ m/yr} \times 20,000 \text{ m}^2 = 2,000 \text{ m}^3/\text{yr}$$

Question 392:

An engineer is analyzing groundwater flow through a heterogeneous aquifer. The hydraulic gradient in one section of the aquifer is measured at 0.03, and the hydraulic conductivity is 12 m/day. What is the groundwater flow velocity in that section?

- A. 0.36 m/day
- B. 0.48 m/day
- C. 0.56 m/day
- D. 0.72 m/day

Answer: A

Explanation: Groundwater flow velocity can be calculated using Darcy's law:

$$v = K \cdot i$$

Where K is hydraulic conductivity and i is hydraulic gradient.

Thus,

$$v = 12 \text{ m/day} \times 0.03 = 0.36 \text{ m/day}$$

Question 393:

A well in an unconfined aquifer is pumped at a rate of 100 L/s. After 48 hours of continuous pumping, the water level in the well has dropped from 15 m to 10 m. What is the total drawdown experienced by the well?

- A. 2 m
- B. 3 m
- C. 4 m
- D. 5 m

Answer: D

Explanation: The drawdown is calculated as:

$$\text{Drawdown} = \text{Initial Water Level} - \text{Final Water Level}$$

Thus,

$$\text{Drawdown} = 15 \text{ m} - 10 \text{ m} = 5 \text{ m}$$

Question 394:

A civil engineer is studying the impact of a wastewater discharge on a river's dissolved oxygen (DO) levels. If the river has a flow rate of $4 \text{ m}^3/\text{s}$ and the DO concentration downstream of the discharge is 5 mg/L , while the upstream concentration is 8 mg/L , what is the total mass of oxygen depleted over a 24-hour period?

- A. 1288 kg
- B. 1576 kg
- C. 1036 kg
- D. 1296 kg

Answer: C

Explanation: The mass of oxygen lost can be calculated as:

$$\text{Mass Loss} = (\text{Upstream DO} - \text{Downstream DO}) \times \text{Flow Rate} \times \text{Time}$$

Where:

$$\text{Mass Loss} = (8 \text{ mg/L} - 5 \text{ mg/L}) \times 4 \text{ m}^3/\text{s} \times 86,400 \text{ s}$$

Convert mg/L to kg/m³:

$$\text{Mass Loss} = 3 \text{ mg/L} \times 4 \times 86,400 = 1036.8 \text{ kg}$$

Question 395:

An environmental scientist is calculating the Total Maximum Daily Load (TMDL) for nitrogen in a river. The current nitrogen load is 2,200 kg/year, and the TMDL is set at 1,500 kg/year. What is the percentage reduction needed to meet the TMDL?

- A. 25%
- B. 32%
- C. 40%
- D. 50%

Answer: B

Explanation: The percentage reduction can be calculated as:

$$\text{Reduction} = \frac{\text{Current Load} - \text{TMDL}}{\text{Current Load}} \times 100$$

Thus,

$$\text{Reduction} = \frac{2200 - 1500}{2200} \times 100 \approx 31.82\%$$

Question 396:

A lake has a total phosphorus concentration of 0.15 mg/L. If the lake has a

volume of 500,000 m³, what is the total phosphorus load in kilograms?

- A. 10.75 kg
- B. 11.25 kg
- C. 15.00 kg
- D. 75.0 kg

Answer: D

Explanation: The total phosphorus load can be calculated as:

$$\text{Load} = \text{Concentration} \times \text{Volume}$$

Convert concentration to kg/m³:

$$\text{Load} = 0.15 \text{ mg/L} \times 500,000 \text{ m}^3 = 75 \text{ kg}$$

Question 397:

In a groundwater contamination study, a monitoring well shows a concentration of benzene at 5 µg/L. If the well extracts water at a rate of 10 L/min, what is the total mass of benzene extracted in a 30-minute sampling period?

- A. 0.15 mg
- B. 0.25 mg
- C. 0.50 mg
- D. 1.50 mg

Answer: D

Explanation: The total mass can be calculated as:

$$\text{Mass} = \text{Concentration} \times \text{Flow Rate} \times \text{Time}$$

Convert flow rate to L/h:

$$\text{Mass} = 5 \mu\text{g}/L \times 10 L/\text{min} \times 30 \text{ min} = 1,500 \mu\text{g} = 1.5 \text{ mg}$$

Question 398:

A civil engineer is evaluating a stream's health by assessing its biological oxygen demand (BOD). If the natural BOD of the stream is 4 mg/L and the BOD after a pollutant influx is measured at 12 mg/L, what is the increase in BOD due to the pollutants?

- A. 4 mg/L
- B. 6 mg/L
- C. 8 mg/L
- D. 10 mg/L

Answer: C

Explanation: The increase in BOD is calculated as:

$$\text{Increase in BOD} = \text{Post-Pollution BOD} - \text{Natural BOD}$$

Thus,

$$\text{Increase in BOD} = 12 \text{ mg/L} - 4 \text{ mg/L} = 8 \text{ mg/L}$$

Question 399:

A groundwater model reveals that a well has a drawdown of 3 m after 24 hours of pumping at a rate of 80 L/s. If the well has a radius of 0.15 m, what is the specific capacity of the well in L/s/m?

- A. 15.33 L/s/m
- B. 26.67 L/s/m
- C. 10.00 L/s/m
- D. 12.00 L/s/m

Answer: B

Explanation: Specific capacity can be calculated using:

$$\text{Specific Capacity} = \frac{\text{Discharge Rate}}{\text{Drawdown}}$$

Thus,

$$\text{Specific Capacity} = \frac{80 \text{ L/s}}{3 \text{ m}} \approx 26.67 \text{ L/s/m}$$

Question 400:

An environmental engineer is assessing the impact of nutrient runoff on a pond. If the pond has a surface area of 1 hectare and receives 15 kg of phosphorus from runoff annually, what is the concentration of phosphorus in mg/L, assuming an average depth of 2 m?

- A. 0.15 mg/L
- B. 0.75 mg/L
- C. 91.00 mg/L
- D. 750 mg/L

Answer: D

Explanation: Convert area to square meters:

$$\text{Area} = 1 \text{ hectare} = 10,000 \text{ m}^2$$

The volume of the pond is:

$$\text{Volume} = \text{Area} \times \text{Depth} = 10,000 \text{ m}^2 \times 2 \text{ m} = 20,000 \text{ m}^3$$

Convert kg to mg:

$$\text{Concentration} = \frac{15 \text{ kg} \times 1,000,000 \text{ mg/kg}}{20,000 \text{ m}^3} = 750 \text{ mg/L}$$

Question 401:

A stream has a flow rate of $1.5 \text{ m}^3/\text{s}$ and a dissolved oxygen (DO) concentration of 9 mg/L upstream. If the DO concentration drops to 5 mg/L downstream after discharge from a wastewater treatment plant, what is the total mass of oxygen lost in kilograms over 24 hours?

- A. 518.4 kg
- B. 288 kg
- C. 864 kg
- D. 1,728 kg

Answer: A

Explanation: The mass of oxygen lost can be calculated as:

$$\text{Mass Loss} = (\text{Upstream DO} - \text{Downstream DO}) \times \text{Flow Rate} \times \text{Time}$$

Thus,

$$\text{Mass Loss} = (9 \text{ mg/L} - 5 \text{ mg/L}) \times 1.5 \text{ m}^3/\text{s} \times 86,400 \text{ s}$$

Convert mg/L to kg/m^3 :

$$\text{Mass Loss} = 4 \text{ mg/L} \times 1.5 \text{ m}^3/\text{s} \times 86,400 \text{ s} = 518,400 \text{ mg} = 518.4 \text{ kg}$$

Question 402:

In a water quality assessment, a river's total nitrogen concentration is measured at 12 mg/L . If the river has a flow rate of $2.5 \text{ m}^3/\text{s}$, what is the total nitrogen load in kilograms per day?

- A. 1250 kg/day
- B. 1300 kg/day
- C. 1036 kg/day
- D. 1600 kg/day

Answer: C

Explanation: The nitrogen load can be calculated as:

$$\text{Load} = \text{Concentration} \times \text{Flow Rate} \times \text{Time}$$

Thus,

$$\text{Load} = 12 \text{ mg/L} \times 2.5 \text{ m}^3/\text{s} \times 86,400 \text{ s} = 1,036,800 \text{ mg} = 1,036.8 \text{ kg}$$

Killexams.com is a leading online platform specializing in high-quality certification exam preparation. Offering a robust suite of tools, including Exam Questions, practice tests, and advanced test engines, Killexams.com empowers candidates to excel in their certification exams. Discover the key features that make Killexams.com the go-to choice for exam success.



Practice Exam Questions Based on Current Exam Objectives

Killexams.com provides practice exam questions aligned with the latest official exam objectives and latest syllabus. Our content is reviewed and updated regularly to reflect recent changes announced by certification vendors. By studying these practice questions, candidates will cover the structure, difficulty level, and topics of the actual exam, helping them prepare more effectively and efficiently.

Comprehensive Practice Exams (PDF Format)

Killexams.com offers multiple-choice questions (MCQs) in easy-to-read PDF format, covering all major domains of the exam. Each PDF contains a structured collection of practice questions and verified answers designed to support focused study. These MCQs help candidates reinforce key concepts, identify knowledge gaps, and improve exam readiness through consistent practice.

Realistic Practice Tests (Online Test Engine & Desktop Test Engine)

To support hands-on preparation, Killexams.com provides practice tests through both an Online Test Engine and a Desktop Test Engine. These tools are designed to simulate a real exam environment, allowing candidates to practice under exam-like conditions, with latest syllabus and topics of the exam. Performance tracking, test history, and result analysis help users evaluate their progress and focus on areas that need improvement.

Risk-Free Purchase Policy

Killexams.com follows a transparent and customer-friendly purchase policy. If users are not satisfied with the study materials, they may request assistance or a refund in accordance with our published terms and conditions. This policy reflects our commitment to customer satisfaction, fairness, and confidence in our preparation resources.

Regularly Updated Content

Our practice question bank is reviewed and updated on an ongoing basis to stay aligned with the latest exam outlines and vendor updates. This ensures candidates are studying up-to-date, relevant material, and preparing with content that reflects current exam expectations, helping them stay confident and well-prepared.